

9353 Seymour Ave | Schiller Park, IL 60176 Toll Free (800) 621-4173 • info@atlasscreensupply.com

www.atlasscreensupply.com

Stretch White 301

Technical Data Sheet

- Wet Ink Tack | Low
- After Flash Tack | Low
- Printability | Excellent
- Surface Appearance | Matte
- Opacity/Viscosity | Excellent/Low
- Bleed Resistance | None
- Flash Temperature | 160°F (71°C)/decreases with deposit thickness
- Cure Temperature | 320°F (160°C)
- Squeegee Hardness | Medium
- Squeegee Blade | Sharp
- Squeegee Angle | 45 degrees to screen
- Squeegee Speed | Medium
- Underlay | Excellent
- Emulsion | Direct or indirect
- Mesh Count | 86-160 mc in (34-63 mc cm)
- Thinner | RV Additive
- Thickener | Thickener B
- Storage | 65°F to 95°F (18°C to 35°C). Avoid direct sun.
- Cleanup | Water and mild soap or detergent
- Color Range | White
- Substrate Type | Cotton
- Substrate Color(s) | Light,
 Medium and Dark Fabrics

Description

Stretch White 301 is a direct print and mixing white for "Performance" and high stretch fabrics that can be mixed with "Neo Pigments" to achieve an extremely soft hand feel and excellent elasticity.

Features

- Easy to mix and print
- Can be used as a mixing white with Neo Pigments up to 15%
- Excellent printability with no viscosity modifications
- Extremely soft hand feel that PVC inks cannot achieve
- Excellent elasticity, great on Dri-fit performance fabrics
- Creates an opaque white print and superb softness
- OEKO-TEX® Standard 100 certified, CPSIA and HR4040 Compliant
- Is "PVC Free" and environmentally safe

Application

Print through fine screen mesh up to 160 mc in (63 mc cm) when cured at 320°F (160°C), **Stretch White 301** produces the softest prints achievable in textile screen printing today.

Special Recommendations

<u>Stretch White 301</u> should be mixed in clean vessels using clean mixing blades and utensils. Any contamination from other ink sources or non-approved additives could make <u>Stretch White 301</u> test positive for restricted PVC's.

- Stretch White 301 can be dry cleaned or ironed
- Use Retarder MG 1-5% to help with open time in the screen
- Use Fixer WF-N 1-5% to help with wash fastness
- Use Softener MG 1-4% to help penetrate in to the garment
- Use Thickener B .25-1% to help thicken the ink
- Use RV Additive 1-3% to reduce viscosity