



MATERIAL SAFETY DATA SHEET

SECTION 1 — PRODUCT IDENTIFICATION

Product identifier: Safe-T-Tack Water Based Adhesive

Product Code: 1081, 1082, 1083 & 1085

DOT Name & Number: Non-Regulated Material N.O.S., Non-Hazardous, No ID #

Date of Preparation: 4/29/03

Revision Date: 7/15/04

Supplier name and address:

ALBATROSS USA INC./EXPERT WORLDWIDE

36-41 36th Street
Long Island City, New York
United States
11106
718-392-6272

5439 San Fernando Road West
Los Angeles, California
United States
90039
818-543-5850

Emergency Telephone #: Chemtrec (Day or Night) 800-424-9300
(For Chemical Emergency: Spill, Leak, Fire, Exposure or Accident)

This MSDS complies with 29CFR 19190.1200 (Hazard Communication Standard) and WHMIS regulations.

IMPORTANT: Read this MSDS before handling and disposing of this product. Pass this information on to employees, customers, and users of this product.

SECTION 2 — HAZARDOUS INGREDIENTS

THE FOLLOWING * ARE REPORTABLE UNDER SARA TITLE III-SECTION 313

Top Five and/or Hazardous Ingredients

<u>CAS #</u>	<u>ACGIH TLV</u>	<u>OSHA PEL</u>	
Water	7732-18-5	Infinite	Infinite
Vinyl Acetate <0.30 %	* 108-05-4	10	20 ppm
Distillates (Petroleum) < 0.1 %			
TSR #1397250002-5310P			
TSR #1397250002-5080P			
TSR #1397250002-5515P			

*Above exposure limits are for air levels only. When skin contact occurs, overexposure may result though air levels are less than limits listed above.

SECTION 3 — PHYSICAL DATA

Odor and Appearance: Opaque white liquid. Characteristic mild laxative odor.
Specific Gravity: 0.99 – 1.03

Vapour Density: 1.0 – 1.4
Vapour Pressure (mmHg @ Temp): 21-27 @ 20 deg C or 68 deg. F
Boiling Point: 202 – 222 Deg. F
Weight/Gal: 8.23 – 8.26
Volatile Organic Compound #/Gal: 0.00
Volatile Organic Compound KG/Liter: 0.00

SECTION 4 — FIRE AND EXPLOSION HAZARD DATA

Flashpoint and Method Used: N/A
Flammable Limits in Air % : LEL - N/A UEL - N/A
Autoignition Temperature: N/A
Extinguish Media: For dry film use CO 2, foam, dry chemical
Special Fire Fighting Procedure: NIOSH/MSHA approved self-contained breathing apparatus should be used.
 Dry film will burn. Cool exposed surfaces with water spray.
Unusual Fire & Explosion Hazard: N/A

SECTION 5 — REACTIVITY DATA

Stability: Stable
Incompatibility (Materials to Avoid): Water reactive materials such as metallic sodium and potassium & strong oxidizing agents.
Conditions to Avoid: Keep away from oxidizing agents. Coagulates when frozen, acidified, or boiled.
Hazardous Decomposition Products: Oxides of Carbon
Hazardous Polymerization: Will not occur.

SECTION 6 — HEALTH HAZARD DATA

Effects of Overexposure:

Acute: N/A

Chronic: This product contains small amounts of vinyl acetate monomer. Carcinogen. Available evidence suggests that the agent is not likely to cause cancer in humans except under uncommon or unlikely routes of exposure. The International Agency for Research on Cancer (IARC) published a monograph on vinyl acetate (1995). In this monograph IARC indicates “there is inadequate evidence in humans for carcinogenicity of vinyl acetate. There is limited evidence in experimental animals for carcinogenicity of vinyl acetate.” Normally, this lack of conclusive evidence would place a substance in the IARC Category 3 classification (Not classified as a human carcinogen). However, because vinyl acetate is metabolized to acetaldehyde, which has an IARC 2b (Possibly carcinogenic to humans) classification, it also has been listed under Category 2B.

Target Organs: - -

Signs and Symptoms of Exposure: N/A

Conditions Prone to Aggrevation by Exposure: N/A

Carcinogenicity: No

This product contains a chemical known to the State of California to cause cancer, birth defects and/or reproductive harm.

Primary Route(s) of Entry: Eyes, skin, ingestion

Emergency and First Aid Procedures: Utilize the suggested methods listed below. In emergency situations, notify a physician immediately.

Skin: Wash with soap and water. Refer to physician if irritation persists.

Eyes: Flush eyes abundantly with clean water and refer to physician.

Ingestion: Treat symptomatically and refer to physician.

Excessive Inhalation: N/A

SECTION 7 — SPECIAL PRECAUTIONS

Handling & Storage: Store away from heat or hot surfaces. Do not store below 40 Deg. F or above 90 Deg. F.

Other Precautions: N/A

SECTION 8 — SPILL OR LEAK PROCEDURES

For Spills or Released Material: Absorb spill in sand, earth, vermiculite, Oil-Dri, or Sol-Speed-Dri. Shovel absorbed material into steel container and cover.

Waste Disposal Method: Dispose of in accordance with federal, state, and local chemical and solvent waste disposal regulations.

SECTION 9 — SAFE HANDLING AND USE INFORMATION

Respiratory Protection: N/A

Ventilation: As specified

Local Exhaust: Remove vapors during processing.

Mechanical Exhaust: Explosion-proof equipment

Special: N/A

Protective Gloves: No gloves

Eye Protection: Safety glasses

Other Protective Equipment: N/A

Hygienic Practices: Keep area clean. Clean up spills immediately. Practice good personal hygiene.

NOTICE:

The supplier disclaims all expressed or implied warranties of merchantability or fitness for a specific use, with respect to the product or the information provided herein, except for conformation to contracted specifications. All information appearing herein is based upon data obtained from manufacturers and/or recognized technical sources. While the information is believed to be accurate, we make no representations as to its accuracy or sufficiency. Conditions of use are beyond our control, and therefore users are responsible for verifying the data under their own operating conditions to determine whether the product is suitable for their particular purposes and they assume all risks of their use, handling, and disposal of the product. Users also assume all risks in regards to the publication or use of, or reliance upon, information contained herein. This information relates only to the product designated herein, and does not relate to its use in combination with any other material or process.