



SAFETY DATA SHEET

SECTION 1 — MANUFACTURER'S NAME & ADDRESS

Product identifier: AlbaChem® Citrus Screen Opener

Product Number: 1634

Chemical Family: Mixture

Generic Description: Screen Opener

Date Revised: May 15, 2014 (Added GHS Pictograms)

Manufacturer's name and address: Refer to supplier

Supplier name and address:

ALBATROSS USA INC./EXPERT WORLDWIDE

36-41 36th Street
Long Island City, New York
United States
11106
718-392-6272

5439 San Fernando Road West
Los Angeles, California
United States
90039
818-543-5850

Emergency Telephone #: Chemtrec (Day or Night) 800-424-9300
(For Chemical Emergency: Spill, Leak, Fire, Exposure or Accident)

This MSDS complies with OSHA Hazard Communication Standard 29 CFR 1910.1200

IMPORTANT: Read this MSDS before handling and disposing of this product. Pass this information on to employees, customer, and users of this product.

SECTION 2 — HAZARDS IDENTIFICATION



DANGER

Emergency Overview: Product is extremely flammable. Pressurized container may explode when exposed to heat or flame. Contact may cause skin and eye irritation. Mist may cause nose and throat irritation. Ingestion may cause nausea, vomiting, pain, upset stomach, and diarrhea.

Potential health effects: **Skin Contact:** This product may cause irritation to the skin. Prolonged or repeated contact with this product may dry and/or defat the skin. This product may be harmful if it is absorbed through the skin. **Eye Contact:** Liquid or vapors may irritate the eyes. Symptoms may include stinging, tearing, redness, swelling, and blurred vision. Eye contact may lead to permanent damage if not treated promptly. **Ingestion:** This product is harmful if swallowed. Ingestion can cause gastrointestinal irritation, nausea, and diarrhea. **Target Organs:** Central Nervous System, lungs, skin, eyes. **Inhalation:** This product may cause dizziness, nausea, upper respiratory irritation, drowsiness, mental depression or narcosis, difficulty in breathing, irregular heart beats. See Section 8 for recommended exposure limits.

SECTION 3 — COMPOSITION/INFORMATION ON INGREDIENTS

COMPONENT(S)	CAS #	% by Weight
D-Limonene	5989-27-5	30-40%
Odorless Mineral Spirits	64742-48-9	30-40%
Liquefied Petroleum Gas	68476-86-8	15-25%

Refer to Section 8 for exposure limits and recommendations.

SECTION 4 — FIRST AID MEASURES

Skin: For skin contact, wash immediately with soap and water. If irritation persists, get medical attention.

Eye: Immediately flush with plenty of water for at least 15 minutes, holding eyelids open at all times. Get medical attention immediately. **Inhalation:** Move person to non-contaminated air. If the affected person is not breathing, apply artificial respiration. Call a physician if symptoms develop or persist. **Ingestion:** If the material is swallowed, get immediate medical attention or advice. DO NOT induce vomiting. If vomiting occurs naturally, have victim lean forward to reduce risk of aspiration. Seek immediate medical attention. Do not give anything.

SECTION 5 — FIRE FIGHTING MEASURES

Extinguishing Media: Use dry chemical, carbon dioxide, or foam. Use water to cool fire-exposed containers and to protect personnel. Do not direct a solid stream of water or foam into hot, burning pools this may result in frothing and increase fire intensity. **Basic Fire Fighting Procedures:** Dangerous when exposed to heat or flame. This material can be ignited by flame or spark under normal atmospheric condition. Vapors are heavier than air and may travel along the ground to some distant source of ignition and flash back. **Pressurized Container:** May explode when exposed to heat or flame. Empty containers may retain product residue including Flammable or Explosive vapors. DO NOT cut, drill, grind, or weld near full, partially full, or empty product containers. **Dust Explosion Hazard:** None known. **Sensitivity To Mechanical Impact:** Container could potentially burst or be punctured upon mechanical impact, releasing flammable vapors. **Unusual Fire & Explosion Hazards:** During a fire, irritating and highly toxic gases may be generated during combustion or decomposition. High temperatures can cause sealed containers to rupture due to a build up of internal pressures. Cool with water. **Fire Fighting Equipment/Instructions:** Wear full protective clothing, including helmet, self-contained positive pressure or pressure demand breathing apparatus, protective clothing and face mask.

Flash Point: concentrate: 120F° propellant: -156 F

Flammability limits in air:

Concentrate:	6.1 upper % by volume concentrate	0.7.% by volume concentrate
Propellant:	9.2 upper % by volume propellant	1.8 lower % by volume propellant

SECTION 6 — ACCIDENTAL RELEASE MEASURES

Emergency Action: Evacuate the area promptly and keep upwind of the spilled material. Isolate the spill area to prevent people from entering. Wear appropriate protective equipment and clothing during clean-up.

Containment: Stop discharge if safe to do so. Stop material from contaminating soil or from entering sewers or water streams. Cover spills with non-flammable absorbent and place in closed chemical waste containers.

SECTION 7 — HANDLING & STORAGE

Handling: Keep this product away from heat, sparks or open flame. Avoid getting this material into contact with your skin and eyes. Avoid breathing mists or aerosols of this product. Use this product with adequate ventilation. Do not reuse the empty container. **Storage:** Store in a cool, dry, well-ventilated area. Do not handle or store near an open flame, heat or other sources of ignition. Keep out of direct sunlight. Do not store above 120F (49 C).

Empty Container Precautions: Attention! Follow label warnings even after container is emptied since empty containers may retain product residues. Do not reuse empty container.

SECTION 8 — EXPOSURE CONTROLS / PERSONAL PROTECTION

Engineering Controls: Provide local and general exhaust ventilation to effectively remove and prevent buildup of any vapors or mists generated from the handling of this product. **Eye Protection:** Wear goggles or safety glasses with side shields. **Skin and Body Protection:** Impervious gloves should be used when handling this product. Use of protective coveralls and long sleeves is recommended. **Respiratory Protection:** Use NIOSH approved respiratory protection. High airborne concentrations may necessitate the use of self-contained breathing apparatus (SCBA). **General:** Use good hygiene practices in handling this material.

Exposure Limits:	(PARTS PER MILLION)					
Component(s)	TLV	OSHA-PEL	OSHA-STEL	SARA 313	Prop 65	VOC
D-Limonene	30 ppm					X
Odorless Mineral Spirits	177 ppm					X
Liquefied Petroleum Gas	1000 ppm					X

Other raw material is considered trade secret.

SECTION 9 — PHYSICAL & CHEMICAL PROPERTIES

Solids: N/A	Evaporation Rate: >1 (butyl acetate=1)
pH: N/A	Boiling Point: N/A
Specific Gravity: 0.678	Color: Clear
Physical State: Liquid	Odor: Citrus
%VOC: 100%	

SECTION 10 — STABILITY & REACTIVITY

Hazardous polymerization will not occur. Condition to avoid: Keep away from sources of ignition. Avoid contact with strong oxidizers, reducers, acids, and alkalis. Stability: This product is stable under normal conditions.

SECTION 11 — TOXICOLOGICAL INFORMATION

D-Limonene:	Oral LD50: >5 g/kg (rat) Dermal LD50: >5 g/kg (rabbit)
Odorless Mineral Spirits:	Oral LD50: >10000 mg/kg (rat) Dermal LD50: >3160 mg/kg (rabbit)
Liquefied Petroleum Gas:	Inhalation LC50: 658 mg/L/4H (rat)

SECTION 12 — ECOLOGICAL INFORMATION

No information available

SECTION 13 — DISPOSAL CONSIDERATION

We make no guarantee of warranty of any kind that the use of and/or disposal of this product complies with all local, state, or federal laws. It is also the obligation of each user of the product mentioned herein to determine and comply with the requirements of all applicable statutes.

Waste Disposal: Dispose of waste material according to Local, State, Federal, and Provincial Environmental Regulations. Wastes must be tested using methods described in 40 CFR Part 261 to determine if it meets applicable definitions of hazardous wastes.

SECTION 14 — TRANSPORT INFORMATION

Ground Transportation: (Continental United States, Canada & Mexico): Consumer Commodity ORM-D

Ocean: UN 1950 Class 2.1 Flammable Gas, Limited Quantity

Air: We do NOT recommend this product to be shipped via air. It would need to be repacked by an authorized packing company and the DG would have to be completed by a licensed hazardous material shipping company.

SECTION 15 — REGULATORY INFORMATION

D-Limonene:	TSCA Inventory SARA: 311/312: Acute Health Hazard Fire Hazard
Odorless Mineral Spirits:	TSCA Inventory. SARA 311/312: Fire Hazard
Liquefield Petroleum Gas:	TSCA Inventory

SECTION 16 — OTHER INFORMATION

H.M.I.S CODES:
HEALTH: 1
FLAMMABILITY: 3
PHYSICAL HAZARD: 0
PERSONAL PROTECTION: C

C=Safety Goggles, gloves and protective wear.

The information in this MATERIAL SAFETY DATA SHEET is pursuant to 29 CFR 1910.1200 to convey information concerning the hazardous nature of this product. The information supplied was compiled from the most reliable sources available at the time of preparation and in light of the most reasonable foreseeable exposure situations expected from the intended use of this product. The material(s) may present greater or lesser hazard

under other circumstances that are beyond the control of the manufacturer. Therefore it is imperative that all direction and warnings on the label be read and understood